

AMENDMENT UNDER 37 C.F.R. § 1.116
Appln. No. 09/601,078

Docket No. Q60201
Art Unit 1733

a block-shaped land portion having a sipe, said block-shaped land portion being defined on a tread surface by main grooves formed in the tire circumferential direction and by lug grooves formed in a direction intersecting with the main grooves;

wherein said sipe is shaped so as to be twisted around a first central axis of twisting extending in a tire radial direction in the block shaped land portion and a second central axis of twisting extending substantially in a tire transverse direction, a position P1 of said first central axis of twisting in a region between one end surface of the block-shaped land portion and another end surface in the tire transverse direction and a position P2 of said central axis of twisting in a region between a contact patch area and a bottom of the sipe in the tire radial direction being within ranges satisfying the following expressions:

$$0.2W \leq P1 \leq 0.8W$$

$$0.2F \leq P2 \leq 0.6F$$

wherein P1, P2 represent the position of the first and second central axes of twisting; W represents a distance from one end surface to the other end surface of the block-shaped land portion in the tire transverse direction; and F represents a distance from the contact patch area to the bottom of the sipe in the tire radial direction; and

wherein the sipe is twisted such that a self alignment torque is generated by the block so as to reduce a self alignment torque generated due to the cords provided parallel to each other in an outermost reinforcing layer of the plurality of reinforcing layers.

2. (Amended) A pneumatic tire comprising:

AMENDMENT UNDER 37 C.F.R. § 1.116
Appln. No. 09/601,078

Docket No. Q60201
Art Unit 1733

a plurality of reinforcing layers in each of which cords, which are inclined at a predetermined angle with respect to a tire circumferential direction, are provided parallel to each other;

a tread provided on a top of said reinforcing layers which are laminated; and

a block-shaped land portion having a sipe, said block-shaped land portion being defined on a tread surface by main grooves formed in the tire circumferential direction and by lug grooves formed in a direction intersecting with the main grooves;

C₁
END
wherein said sipe is shaped so as to have a first protruding portion protruding in a first direction with respect to a virtual central plane and a second protruding portion protruding in a second direction opposite the first direction across the virtual central plane, said sipe including a surface portion exposed on a contact patch area of said block-shaped land portion and a bottom portion formed in a bottom of the sipe, the virtual central plane and thereby said sipe being twisted from the surface portion toward the bottom portion; and

wherein the sipe is twisted such that a self alignment torque is generated by the block so as to reduce a self alignment torque generated due to the cords provided parallel to each other in an outermost reinforcing layer of the plurality of reinforcing layers.

7. (Amended) A pneumatic tire comprising:

C₂
a plurality of reinforcing layers in each of which cords, which are inclined at a predetermined angle with respect to a tire circumferential direction, are provided parallel to each other;

AMENDMENT UNDER 37 C.F.R. § 1.116
Appln. No. 09/601,078

Docket No. Q60201
Art Unit 1733

a tread provided on a top of said reinforcing layers which are laminated; and
a block-shaped land portion having a sipe, said block-shaped land portion being defined on a tread surface by main grooves formed in the tire circumferential direction and by lug grooves formed in a direction intersecting with the main grooves;

C₂
END
wherein said sipe is shaped as a closed loop which is connected with neither said main groove nor said lug groove, said sipe including a surface portion exposed on a contact path area of the block shaped land portion and a bottom portion formed in a bottom of a sipe, the sipe being twisted from said surface portion toward said bottom portion; and

wherein the sipe is twisted such that a self alignment torque is generated by the block so as to reduce a self alignment torque generated due to the cords provided parallel to each other in an outermost reinforcing layer of the plurality of reinforcing layers.
